

Description	Product	ASTM	Thickness	Color			Sizes		Area per Roll	Weight per Roll	Specifications		Guarantees
				White	Grey	Tan	Width x Length	Mechanically Fastened			Adhered	All Systems	
Thermoplastic, polyester reinforced membrane manufactured using an ultraviolet-resistant TPO (thermoplastic polyolefin) formulation.	JM TPO	D 6878	45 mil	X	*	*	5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	133 lb (58.97 kg)	ST4RM	ST4RA	5, 10, or 15 yr NDL	
				X			6' x 100' (1.83 m x 30.48 m)	600 ft <sup>2</sup> (55.74 m <sup>2</sup> )	160 lb (72.57 kg)				
				X	*	*	8' x 100' (2.44 m x 30.48 m)	800 ft <sup>2</sup> (74.32 m <sup>2</sup> )	210 lb (95.25 kg)				
				X	*	*	10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	265 lb (120.2 kg)				
				X			12' x 100' (3.66 m x 30.48 m)	1,200 ft <sup>2</sup> (111.5 m <sup>2</sup> )	318 lb (144.2 kg)				
			60 mil	X	X	X	5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	173 lb (78.47 kg)	ST6RM ST6RR	ST6RA	5, 10, 15, or 20 yr NDL	
				X	*	*	6' x 100' (1.83 m x 30.48 m)	600 ft <sup>2</sup> (55.74 m <sup>2</sup> )	208 lb (94.35 kg)				
				X	X	*	8' x 100' (2.44 m x 30.48 m)	800 ft <sup>2</sup> (74.32 m <sup>2</sup> )	275 lb (124.7 kg)				
				X	X	X	10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	345 lb (156.5 kg)				
				X	X	*	12' x 100' (3.66 m x 30.48 m)	1,200 ft <sup>2</sup> (111.5 m <sup>2</sup> )	414 lb (187.8 kg)				
			80 mil	X	X	X	5' x 75' (1.52 m x 22.86 m)	375 ft <sup>2</sup> (34.84 m <sup>2</sup> )	173 lb (78.47 kg)	ST8RM ST8RR	ST6RA	5, 10, 15, 20, or 25 yr NDL 30 yr STRA	
				X			6' x 75' (1.83 m x 22.86 m)	450 ft <sup>2</sup> (41.81 m <sup>2</sup> )	208 lb (94.35 kg)				
				X	*	*	8' x 75' (2.44 m x 22.86 m)	600 ft <sup>2</sup> (55.74 m <sup>2</sup> )	275 lb (124.7 kg)				
				X	X	X	10' x 75' (3.05 m x 22.86 m)	750 ft <sup>2</sup> (69.68 m <sup>2</sup> )	375 lb (170.1 kg)				
				X			12' x 75' (3.66 m x 22.86 m)	900 ft <sup>2</sup> (83.61 m <sup>2</sup> )	415 lb (188.2 kg)				
Thermoplastic polyolefin (TPO) membrane with a reinforced internal polyester fabric and integral 3.5 oz polyester fleece backing.	JM TPO FB 115™	D 6878	60 mil	X	*	*	10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	385 lb (174.6 kg)	ST6PM	ST6PA ST6PU	5, 10, 15, or 20 yr NDL	
	JM TPO FB 135™		80 mil	X	*	*	10' x 50' (3.05 m x 15.24 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	265 lb (120.2 kg)	ST8PM	ST8PA ST8PU	5, 10, 15, 20, or 25 yr NDL 30 yr STPA	
Thermoplastic polyolefin (TPO) membrane with a reinforced internal polyester fabric and integral 8 oz polyester fleece backing for hot moppable applications.	JM TPO FB 150™	D 6878	60 mil	X	*	*	10' x 75' (3.05 m x 22.86 m)	750 ft <sup>2</sup> (69.68 m <sup>2</sup> )	355 lb (161.0 kg)	N/A	2, 3 or 4GIT-T6 2, 3 or 4CIT-T6 2, 3 or 4PIT-T6 2, 3 or 4FIT-T6	5, 10, 15, or 20 yr NDL	
	JM TPO FB 175™		80 mil	X	*	*	10' x 50' (3.05 m x 15.24 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	277 lb (125.6 kg)	N/A	2, 3 or 4GIT-T8 2, 3 or 4CIT-T8 2, 3 or 4PIT-T8 2, 3 or 4FIT-T8	5, 10, 15, 20, or 25 yr NDL 30 yr STPA	
Thermoplastic polyolefin (TPO) membrane with a reinforced internal polyester fabric and a pressure sensitive adhesive applied for self-adhering applications.	JM TPO SA	D 6878	60 mil	X			5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	198 lb (89.81 kg)	N/A	ST6RA	5, 10, 15, or 20 yr NDL	
				X			10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	396 lb (179.6 kg)	N/A			

\*Grey and Tan are special order. These colors require minimum quantities and have extended lead-times. Please contact your JM sales representative for further information.